

# VALVULAS Y CONEXIONES INDUSTRIALES, S.A. DE C.V.

## Especificaciones de tubería de acero.



Medida	Diametro Exterior	Espesor	Diametro Interior	Cedula	Peso KG/MTO
1/8"	0.405	0.049	0.307	10	
1/8"	0.405	0.057	0.291	30	
1/8"	0.405	0.068	0.269	40	0.37
1/8"	0.405	0.095	0.215	80	0.47
1/4"	0.54	0.065	0.41	10	
1/4"	0.54	0.073	0.394	30	
1/4"	0.54	0.88	0.364	40	0.63
1/4"	0.54	0.119	0.302	80	0.8
3/8"	0.675	0.065	0.545	10	
3/8"	0.675	0.073	0.529	30	
3/8"	0.675	0.091	0.493	40	0.84
3/8"	0.675	0.126	0.423	80	1.1
1/2"	0.84	0.065	0.71	5	
1/2"	0.84	0.083	0.674	10	
1/2"	0.84	0.095	0.65	30	
1/2"	0.84	0.109	0.622	40	1.27
1/2"	0.84	0.147	0.546	80	1.62
1/2"	0.84	0.188	0.464	160	1.95
3/4"	1.05	0.065	0.92	5	
3/4"	1.05	0.093	0.884	10	
3/4"	1.05	0.095	0.86	30	
3/4"	1.05	0.113	0.824	40	1.69
3/4"	1.05	0.154	0.742	80	2.2
3/4"	1.05	0.219	0.612	160	2.9
1"	1.315	0.065	1.185	5	
1"	1.315	0.109	1.097	10	
1"	1.315	0.114	1.084	30	
1"	1.315	0.133	1.049	40	2.5
1"	1.315	0.179	0.957	80	3.24
1"	1.315	0.25	0.815	160	4.24
1 1/4"	1.66	0.065	1.53	5	
1 1/4"	1.66	0.109	1.442	10	
1 1/4"	1.66	0.117	1.426	30	
1 1/4"	1.66	0.14	1.38	40	3.39
1 1/4"	1.66	0.191	1.278	80	4.47
1 1/4"	1.66	0.25	1.16	160	5.61
1 1/2"	1.9	0.065	1.77	5	
1 1/2"	1.9	0.109	1.682	10	

# VALVULAS Y CONEXIONES INDUSTRIALES, S.A. DE C.V.

## Especificaciones de tubería de acero.



Medida	Diametro Exterior	Espesor	Diametro Interior	Cedula	Peso KG/MTO
1 1/2"	1.9	0.125	1.65	30	
1 1/2"	1.9	0.145	1.61	40	4.05
1 1/2"	1.9	0.2	1.5	80	5.41
1 1/2"	1.9	0.281	1.338	160	7.24
2"	2.375	0.065	2.245	5	
2"	2.375	0.109	2.157	10	3.93
2"	2.375	0.125	2.125	30	4.48
2"	2.375	0.154	2.067	40	5.44
2"	2.375	0.218	1.939	80	7.48
2"	2.375	0.344	1.687	160	11.11
2 1/2"	2.875	0.093	2.709	5	
2 1/2"	2.875	0.12	2.635	10	
2 1/2"	2.875	0.188	2.499	30	8.04
2 1/2"	2.875	0.203	2.469	40	8.63
2 1/2"	2.875	0.276	2.323	80	11.41
2 1/2"	2.875	0.375	2.125	160	14.92
2 1/2"	2.875	0.552	1.771	XXS	20.4
3"	3.5	0.083	2.708	5	4.52
3"	3.5	0.12	2.635	10	
3"	3.5	0.188	2.499	30	9.92
3"	3.5	0.203	2.469	40	11.29
3"	3.5	0.276	2.323	80	15.27
3"	3.5	0.375	2.125	160	21.34
3"	3.5	0.6	1.774	XXS	27.68
3 1/2"	4	0.093	3.834	5	
3 1/2"	4	0.12	3.76	10	
3 1/2"	4	0.188	3.624	30	11.41
3 1/2"	4	0.237	3.548	40	13.57
3 1/2"	4	0.337	3.5	80	22.32
3 1/2"	4	0.531	3.438	160	33.53
3 1/2"	4	0.674	3.364	XXS	41.03
4"	4.5	0.083	4.334	5	5.84
4"	4.5	0.12	4.26	10	
4"	4.5	0.188	4.124	30	12.91
4"	4.5	0.237	4.026	40	16.07
4"	4.5	0.337	3.826	80	22.32
4"	4.5	0.438	3.624	120	28.32
4"	4.5	0.531	3.438	160	33.54

# VALVULAS Y CONEXIONES INDUSTRIALES, S.A. DE C.V.

## Especificaciones de tubería de acero.



Medida	Diametro Exterior	Espesor	Diametro Interior	Cedula	Peso KG/MTO
4"	4.5	0.674	3.152	XXS	41.03
5"	5.563	0.109	5.345	5	
5"	5.563	0.134	5.295	10	
5"	5.563	0.258	5.047	40	21.78
5"	5.563	0.375	4.813	80	30.95
5"	5.563	0.5	4.563	120	40.28
5"	5.563	0.625	4.313	160	49.11
6"	6.625	0.109	6.407	5	11.31
6"	6.625	0.144	6.357	10	
6"	6.625	0.28	6.065	40	28.27
6"	6.625	0.432	5.761	80	42.57
6"	6.625	0.562	5.501	120	54.2
6"	6.625	0.719	5.187	160	67.57
6"	6.625	0.864	4.897	XXS	79.22
8"	8.625	0.109	8.407	5	
8"	8.625	0.148	8.329	10	
8"	8.625	0.25	8.125	20	
8"	8.625	0.277	8.071	30	36.79
8"	8.625	0.322	7.981	40	42.54
8"	8.625	0.406	7.813	60	53.09
8"	8.625	0.5	7.625	80	64.63
8"	8.625	0.594	7.437	100	75.69
8"	8.625	0.719	7.187	120	90.44
8"	8.625	0.812	7.001	140	100.08
8"	8.625	0.906	6.813	160	111.27
10"	10.75	0.134	10.482	5	
10"	10.75	0.165	10.42	10	
10"	10.75	0.25	10.25	20	
10"	10.75	0.307	10.136	30	51.01
10"	10.75	0.365	10.2	40	60.31
10"	10.75	0.5	9.75	60	81.54
10"	10.75	0.594	9.562	80	95.83
10"	10.75	0.719	9.312	100	114.75
10"	10.75	0.844	9.062	120	133.02
10"	10.75	1	8.75	140	155.15
10"	10.75	1.125	8.5	160	172.33
12"	12.75	0.156	12.438	5	
12"	12.75	0.18	12.39	10	

# VALVULAS Y CONEXIONES INDUSTRIALES, S.A. DE C.V.

## Especificaciones de tubería de acero.



Medida	Diametro Exterior	Espesor	Diametro Interior	Cedula	Peso KG/MTO
12"	12.75	0.25	12.25	20	
12"	12.75	0.33	12.09	30	65.21
12"	12.75	0.375	12	STD	73.83
12"	12.75	0.406	11.938	40	79.73
12"	12.75	0.562	11.626	60	108.98
12"	12.75	0.688	11.374	80	132.03
12"	12.75	0.844	11.062	100	159.87
12"	12.75	1	10.75	120	186.7
12"	12.75	1.125	10.5	140	207.9
12"	12.75	1.32	10.126	160	238.76
14"	14	0.165	13.688	5	
14"	14	0.25	13.5	10	
14"	14	0.312	13.376	20	67.91
14"	14	0.375	13.25	30	81.33
14"	14	0.438	13.124	40	94.51
14"	14	0.5	13	XS	107.39
14"	14	0.594	12.812	60	126.71
14"	14	0.75	12.5	80	158.1
14"	14	0.938	12.124	100	194.5
14"	14	1.094	11.812	120	224.2
14"	14	1.25	11.5	140	253.3
14"	14	1.406	11.188	160	281.4
16"	16	0.165	15.67	5	
16"	16	0.25	15.5	10	
16"	16	0.312	15.376	20	
16"	16	0.375	15.25	30	93.22
16"	16	0.5	15	40	123.3
16"	16	0.656	14.688	60	160.12
16"	16	0.844	14.312	80	203.53
16"	16	1.031	13.938	100	245.56
16"	16	1.219	13.562	120	286.64
16"	16	1.438	13.124	140	333.19
16"	16	1.594	12.812	160	365.35
18"	18	0.165	17.67	5	
18"	18	0.25	17.5	10	
18"	18	0.312	17.376	20	
18"	18	0.438	17.124	30	
18"	18	0.562	16.876	40	155.92

# VALVULAS Y CONEXIONES INDUSTRIALES, S.A. DE C.V.

## Especificaciones de tubería de acero.



Medida	Diametro Exterior	Espesor	Diametro Interior	Cedula	Peso KG/MTO
18"	18	0.75	16.5	60	205.83
18"	18	0.938	16.124	80	254.62
18"	18	1.156	15.688	100	309.62
18"	18	1.375	15.25	120	363.56
18"	18	1.562	14.876	140	408.26
18"	18	1.781	14.438	160	459.37
20"	20	0.188	19.624	5	
20"	20	0.25	19.5	10	
20"	20	0.375	19.25	20	117.09
20"	20	0.5	19	30	155.12
20"	20	0.594	18.812	40	183.39
20"	20	0.812	19.376	60	247.88
20"	20	1.031	17.938	80	311.53
20"	20	1.281	17.438	100	381.53
20"	20	1.5	17	120	441.49
20"	20	1.75	16.5	140	507.6
20"	20	1.969	16.062	160	564.81
22"	22	0.188	21.624	5	
22"	22	0.25	21.5	10	
22"	22	0.375	21.25	20	
22"	22	0.5	21	30	
22"	22	0.845	20.25	60	
22"	22	1.125	19.75	80	
22"	22	1.375	19.25	100	
22"	22	1.625	18.75	120	
22"	22	1.875	17.25	140	
22"	22	2.125	17.75	160	
24"	24	0.218	23.654	5	
24"	24	0.25	23.5	10	
24"	24	0.375	23.25	20	141.12
24"	24	0.562	22.876	30	
24"	24	0.688	22.624	40	255.41
24"	24	0.969	22.062	60	355.3
24"	24	1.219	21.562	80	442.08
24"	24	1.531	20.938	100	547.71
24"	24	1.812	20.376	120	640.03
24"	24	2.062	19.876	140	720.15
24"	24	2.344	19.312	160	808.22

# VALVULAS Y CONEXIONES INDUSTRIALES, S.A. DE C.V.

## Especificaciones de tubería de acero.



Medida	Diametro Exterior	Espesor	Diametro Interior	Cedula	Peso KG/MTO
26"	26	0.312	25.376	10	
26"	26	0.5	25	20	
28"	28	0.312	27.376	10	
28"	28	0.5	27	20	
28"	28	0.625	26.75	30	
30"	30	0.25	29.5	5	118.33
30"	30	0.312	28.376	10	376.98
30"	30	0.5	29	20	234.67
30"	30	0.625	28.75	30	292.18
32"	30	0.312	31.376	10	
32"	30	0.5	31	20	
32"	30	0.625	30.75	30	
32"	30	0.688	30.624	40	
34"	34	0.312	33.376	10	
34"	34	0.5	33	20	
34"	34	0.625	32.75	30	
34"	34	0.688	32.624	40	
36"	36	0.312	35.376	10	
36"	36	0.5	35	20	
36"	36	0.625	34.75	30	
36"	36	0.75	34.5	40	